

PRODUCT DATA SHEET

SikaTop®-107 Plus

CEMENTITIOUS WATERPROOFING COATING PLUS - 2 COMPONENT

DESCRIPTION

SikaTop®-107 Plus is a two component, pre-packed polymer modified cementitious waterproofing slurry mortar comprising of a liquid polymer and cement with selected grades of sand and several admixtures. It has excellent adhesion and high performance.

USES

For external and internal waterproofing, crack sealing, on concrete, mortar, brickwork, and steel in:

- Swimming pool
- Water tank
- Fish pond
- Toilet
- Balcony

CHARACTERISTICS / ADVANTAGES

- With composition that easy to apply
- Good impermeable
- Excellent adhesion and good resistance to abrasion
- Non-toxic for drinking water tank, fish pond, and swimming pool
- Slightly flexible
- Factory mixed – consistent quality
- Easy to use and apply, only requires mixing of both material

PRODUCT INFORMATION

Packaging	4 kg set	Comp A (Liquid) = 1 kg
	36 kg set	Comp B (Powder) = 3 kg Comp A (Liquid) = 9 kg Comp B (Powder) = 27 kg
Shelf life	9 months from date of production if stored properly in original, unopened and undamaged sealed packaging	
Storage conditions	Store in dry conditions at temperatures between +5 °C and +30 °C.	
Appearance and colour	FORM	COLOURS
	Comp. A = Liquid Comp. B = Powder	Comp. A = White Comp. B = Grey Comp. A + B = Concrete Grey
Density	~1.95 ± 0.05 kg/L (part A + B mixed)	

TECHNICAL INFORMATION

Compressive strength	28 days = ~10.0 N/mm ²
Tensile strength in flexure	28 days = ~10.0 N/mm ²

APPLICATION INFORMATION

Mixing ratio	Comp. A (liquid) : comp. B (powder) = 1 kg : 3 kg (by weight) Comp. A (liquid) : comp. B (powder) = 1 : 2.25 (by volume)	
Consumption	1 - 1.5 kg set/m ² /coat (using brush, depend on substrate surface) 2 coats always required	
Ambient air temperature	8 °C to 40 °C	
Pot Life	at +30 °C	~30 min

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

- Do not use more than 2 kg/m²/coat
- It is suggested that SikaTop®-107 Plus should be protected with 2-3 cm of cement screed.
- When required to provide a smooth and level surface, levelling screed or render shall be placed before the application of SikaTop®-107 Plus. It is recommended that bonding coat is used (e.g. SikaTop®-77 D : cement : sand = 1:2:1) before screeding.
- If the substrate (that SikaTop®-107 Plus is applied on it) cannot dry, the polymer emulsion of SikaTop®-107 Plus will not be coalesced and will not be cured.
- For tile application on SikaTop®-107 Plus, use Sika® TileFix-200 TA. For optimum result, Sika® TileFix-200 TA should be applied max. 48 hours after SikaTop®-107 Plus application.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

Concrete / screed / plaster surface must be clean, sound, level and uncontaminated by oil or grease. Remove cement laitance, dust, and loosely adhering particles.

Absorbent substrates must be pre-wetted to saturated surface dry (SSD) conditions.

Steel / Iron surface must be clean, free of oil, grease and rust.

MIXING

- Pour approximately 90% of Component A into mixing vessel then add Component B slowly and mix properly.
- Add remaining component A while continuing to mix. Mix to a uniform consistency.
- Mixing time is 3 minutes. A slow speed mixer is recommended (300 – 600 rpm).

APPLICATION

- Apply with brush min. 2 coats.
- After the 1st coat dry (2-6 hours), apply the 2nd coat with a crosswise direction.

IMPORTANT NOTES

Must use component A (liquid) and B (powder) of SikaTop®-107 Plus in 1 set, CANNOT be replaced one of them with other brand or added with other ingredients (water, cement or sand).

CURING TREATMENT

As cement based product, curing is important. Protect the freshly applied product against direct sunlight and strong winds. Use damp hessian or plastic sheet. Protect the applied SikaTop from rain and water splashes until fully hardened (~ 6 hours).

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

PT. Sika Indonesia Head Office and Manufacturing

Jl. Raya Cibinong-Bekasi Km.20
Limusnunggal-Cileungsi
Bogor 16820-Indonesia
Tel. +62 21 8230025, Fax +62 21
8230026



Product Data Sheet

SikaTop®-107 Plus
January 2023, Version 03.01
020701010020000075

SikaTop-107Plus-en-ID-(01-2023)-3-1.pdf

