

PRODUCT DATA SHEET

Sika® BondBreaker ID

A WATER REPELLENT, BOND BREAKER MATERIAL

DESCRIPTION

Sika® BondBreaker ID is a water repellent, bond breaker material.

USES

Sika® BondBreaker ID is used for "match-cast", "tilt-up" and "tilt-slab" constructions.

CHARACTERISTICS / ADVANTAGES

- Easy application by brush or sprayer
- Non - Hazardous, Non Toxic
- Non - Staining
- Does not interfere with concrete placements
- Can be used as mould release agent as well

PRODUCT INFORMATION

Packaging	Pail 20 L Drum 200 L
Appearance / Colour	Milky white / liquid
Shelf life	12 months from the date of production if stored properly in undamaged, original, sealed packaging.
Storage conditions	Store in dry conditions at temperatures between +5 °C and +30 °C. Protect from direct sunlight and frost.
Density	~0.9 ± 0.1 kg/L (at +20 °C)

APPLICATION INFORMATION

Consumption	Apply 1-2 coat(s) at 0.1 - 0.2 L/m ² per coat. When 2 coats are necessary, apply the 2nd coat 1-2 hours after the first coat.
--------------------	--

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

The product shall be applied onto clean dirt-free substrates and leave it dry for 2-3 hours before casting concrete.

IMPORTANT CONSIDERATIONS

For large "tilt-up" and "tilt-slab" application, process, timing and consumption rate must be test for optimal result.

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

PT. Sika Indonesia Head Office and

Jl. Raya Cibinong-Bekasi Km.20
Limusnunggal-Cileungsi
Bogor 16820-Indonesia
Tel. +62 21 8230025, Fax +62 21 8230026
Web: idn.sika.com
Email: sikacare@id.sika.com



SikaBondBreakerID-en-ID-(10-2017)-1-1.pdf

Product Data Sheet
Sika® BondBreaker ID
October 2017, Version 01.01
021405031000000118