

PRODUCT DATA SHEET

Sika® Aggregate-510

AGGREGATE FOR SIKACRETE SYSTEM AND SIKAGROUT SYSTEM

DESCRIPTION

A selection of carefully graded and blended natural aggregates.

USES

Sika® Aggregate-510 have been specifically developed for compatible use with a range of Sikacrete® and SikaGrout® system.

FEATURES

Specifically graded for use with Sikacrete® System and SikaGrout® System

PRODUCT INFORMATION

Packaging	10 kg plastic bag
Appearance and colour	Aggregate / Dark Grey
Shelf life	No shelf life limit if stored in unopened, undamaged and original sealed packaging
Storage conditions	The product must be stored in original, unopened, and undamaged sealed packaging in dry conditions at temperatures between +10 °C and +35 °C. Protect from direct sunlight.
Maximum grain size	10 mm

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

PT. Sika Indonesia Head Office and Manufacturing

Jl. Raya Cibinong-Bekasi Km.20
Limusnunggal-Cileungsi
Bogor 16820-Indonesia
Tel. +62 21 8230025, Fax +62 21
8230026



Product Data Sheet
Sika® Aggregate-510
December 2024, Version 01.02
020302040080000010

SikaAggregate-510-en-ID-(12-2024)-1-2.pdf