

PRODUCT DATA SHEET

Sika® Antisol® E-125

Concrete Curing Compounds

DESCRIPTION

A liquid curing compound for preventing water loss in concrete.

Complies with A.S.T.M. C 309-94 type I, class A.

USES

Sika® Antisol® E-125 is use in large areas of exposed concrete, and suitable for trafficable surfaces such as :

- Highways
- Runways and taxiways
- Aprons and hard standings
- Roof decks
- Retaining walls
- Pre-stressed beams and piers, etc

FEATURES

Sika® Antisol® E-125 provides the following properties :

- Reduces incidence of plastic cracking
- Minimises shrinkage
- Reduces dusting
- Non flammable
- Provides a labour saving method of ensuring all fresh concrete is cured properly

PRODUCT INFORMATION

Composition	Paraffin/wax
Packaging	200 kg drum 20 kg can
Shelf life	9 months from date of production if stored properly in undamaged un-opened, original container.
Storage conditions	Store in dry conditions at temperatures between +5 °C and +35 °C. Protect from direct sunlight and frost.
Appearance and colour	Liquid / White

TECHNICAL INFORMATION

Specific advice

Remaining Antisol films have to be removed prior to application of any screed or coating. After application the treated are must be protected from rain for at least 2 – 3 hours.

- To prevent clogging, regular cleaning of jet sprays during application is recommended
- Sika® Antisol® E-125 can be sprayed using most common spraying equipment
- Sika® Antisol® E-125 should NOT be overcoated with other coating or

treatments. If material is to be applied over the top of surface treated with Sika® Antisol® E-125, sand blasting or solvent treatment is recommended as surface preparation.

- Early application of Sika® Antisol® E-125 will help prevent plastic shrinkage cracks from occurring by reducing the amount of water evaporating. Concrete curing compounds, however, will not counter the effects of cracking that may occur as a result of long term drying shrinkage. Standard concrete practice must be applied when positioning construction joints and shrinkage control joints.

APPLICATION INFORMATION

Consumption	0.15 – 0.20 kg/m ² Depending on wind, temperature, humidity and the roughness of concrete surface.
--------------------	--

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

The surface water of the newly laid concrete must have evaporated (between 1/2 to 2 hours, depending on temperature, etc.).

APPLICATION

Stir well before use !

The Sika® Antisol® E-125 has been designed for spray application to the newly laid concrete. A thin film of Sika® Antisol® E-125 is applied to the whole surface using a hand or spray gun.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

PT. Sika Indonesia Head Office and Manufacturing

Jl. Raya Cibinong-Bekasi Km.20
Limusnunggal-Cileungsi
Bogor 16820-Indonesia
Tel. +62 21 8230025, Fax +62 21
8230026



Product Data Sheet
Sika® Antisol® E-125
February 2024, Version 02.01
02140503100000036

SikaAntisolE-125-en-ID-(02-2024)-2-1.pdf