

PRODUCT DATA SHEET

Sika® MultiSeal

BITUMINOUS SEALING TAPE

DESCRIPTION

Sika® MultiSeal is a self-adhesive, rubber modified bituminous sealing tape laminated with an aluminium foil on the upper side.

USES

Sika® MultiSeal is designed for sealing and repairing applications against water ingress on roofs and any other building element.

CHARACTERISTICS / ADVANTAGES

- Very easy to apply
- Good adhesion to many substrates
- Self-adhering
- Compatible with bituminous substrates
- Can be overpainted
- Can be applied at low temperatures

PRODUCT INFORMATION

Composition	Rubber modified, bituminous tape		
Packaging	Length per roll	Tape width	Rolls per box
	3 m	100 mm	12
Appearance / Colour	Matt grey, terracotta brown		
Shelf life	Sika® MultiSeal has a shelf life of 72 months from the date of production, if it is stored properly in undamaged, original, sealed packaging, and if the storage conditions are met.		
Storage conditions	Sika® MultiSeal shall be stored in dry conditions, protected from direct sunlight and at temperatures between +5 °C and +25 °C.		
Thickness	~1.2 mm		

TECHNICAL INFORMATION

Tensile Strength	~3.6 N/mm ²		
Elongation at Break	~50 %		
Reaction to Fire	B2	(DIN 4102)	
Service Temperature	-20 °C to +70 °C		

APPLICATION INFORMATION

Ambient Air Temperature	+5 °C to +40 °C, min. 3 °C above dew point temperature
Substrate Temperature	+5 °C to +40 °C At temperatures below +10 °C the tape and the substrate must be warmed with a hot air fan before and during the application.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

The substrate must be clean, dry, sound and homogeneous, free from oils, grease, dust and loose or friable particles.

APPLICATION METHOD / TOOLS

Cut the tape to the required length, remove the release film and press the tape firmly onto the substrate with a suitable roller.

For overlapping, ≥ 5 cm is required.

Adhesion performance can be improved by heating Sika® MultiSeal tape during application.

CLEANING OF EQUIPMENT

Clean all tools and application equipment immediately after use with Sika® Remover-208. Once cured, residual material can only be removed mechanically.

IMPORTANT CONSIDERATIONS

- The upper side of Sika® MultiSeal can be over-painted with most conventional paint systems.
- Do not use Sika® MultiSeal on natural stone.
- Do not use Sika® MultiSeal for joints under water pressure or for permanent water immersion.
- Direct contact with joint sealants and adhesives must be avoided or compatibility must be tested prior to application.

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

PT. Sika Indonesia Head Office and

Jl. Raya Cibinong-Bekasi Km.20

Limusnunggal-Cileungsi

Bogor 16820-Indonesia

Tel. +62 21 8230025, Fax +62 21 8230026

Web: idn.sika.com

Email: sikacare@id.sika.com



Product Data Sheet

Sika® MultiSeal

June 2017, Version 01.01

020516050000000009

SikaMultiSeal-en-ID-(06-2017)-1-1.pdf